

# Low Voltage Lampholders *with sealing option*



C1090FP - - -


- ▶ Up to 50V
- ▶ MES or MBC bulb
- ▶ Flat and domed lens
- ▶ Brass or nylon bodies
- ▶ Red, Amber, Green, Blue and Clear lenses
- ▶ Front panel seal option

**RoHS**

RoHS compliant by 3rd qtr 2005


Bulbs will be supplied (dependant on order quantity) if a voltage is specified. These lampholders are suitable for up to 50V max.

Colours - Red, Amber, Green, (Clear & Blue, check availability). Brass bodies have polished chrome finish.



▶ TERMINAL	▶ LAMP CAP	▶ LENS	▶ THREADED BODY																																							
<p><b>C</b></p> <p>6.3 x 0.8</p>	<p><b>1090</b> E10</p>  <p><b>1091</b> BA9s</p>	<p><b>F</b> Flat</p>  <p><b>V</b> Domed</p>  <p><b>L</b> No lens</p>	<table border="1"> <thead> <tr> <th>Panel Hole Dia.</th> <th>Body Material</th> <th>Dimension A</th> </tr> </thead> <tbody> <tr> <td colspan="3" style="text-align: center;">for E10 types</td> </tr> <tr> <td><b>A</b></td> <td>19.0 Brass</td> <td>35.0</td> </tr> <tr> <td><b>D</b></td> <td>19.0 Brass</td> <td>30.2</td> </tr> <tr> <td><b>E</b></td> <td>19.0 Nylon</td> <td>30.2</td> </tr> <tr> <td><b>*P</b></td> <td>19.0 Nylon (+ chrome trim)</td> <td>30.2</td> </tr> <tr> <td><b>G</b></td> <td>19.0 Brass</td> <td>24.6</td> </tr> <tr> <td><b>H</b></td> <td>19.0 Nylon</td> <td>24.6</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Panel Hole Dia.</th> <th>Body Material</th> <th>Dimension A</th> </tr> </thead> <tbody> <tr> <td colspan="3" style="text-align: center;">for BA9s types</td> </tr> <tr> <td><b>B</b></td> <td>19.0 Brass</td> <td>35.0</td> </tr> <tr> <td><b>C</b></td> <td>19.0 Nylon</td> <td>35.0</td> </tr> <tr> <td><b>*Q</b></td> <td>19.0 Nylon (+ chrome trim)</td> <td>35.0</td> </tr> </tbody> </table> <p style="text-align: center; margin-top: 10px;">All E10 and BA9s types are suitable for panel thickness up to 6.2mm. Some versions will accept panels up to 11.2mm thick.</p>	Panel Hole Dia.	Body Material	Dimension A	for E10 types			<b>A</b>	19.0 Brass	35.0	<b>D</b>	19.0 Brass	30.2	<b>E</b>	19.0 Nylon	30.2	<b>*P</b>	19.0 Nylon (+ chrome trim)	30.2	<b>G</b>	19.0 Brass	24.6	<b>H</b>	19.0 Nylon	24.6	Panel Hole Dia.	Body Material	Dimension A	for BA9s types			<b>B</b>	19.0 Brass	35.0	<b>C</b>	19.0 Nylon	35.0	<b>*Q</b>	19.0 Nylon (+ chrome trim)	35.0
Panel Hole Dia.	Body Material	Dimension A																																								
for E10 types																																										
<b>A</b>	19.0 Brass	35.0																																								
<b>D</b>	19.0 Brass	30.2																																								
<b>E</b>	19.0 Nylon	30.2																																								
<b>*P</b>	19.0 Nylon (+ chrome trim)	30.2																																								
<b>G</b>	19.0 Brass	24.6																																								
<b>H</b>	19.0 Nylon	24.6																																								
Panel Hole Dia.	Body Material	Dimension A																																								
for BA9s types																																										
<b>B</b>	19.0 Brass	35.0																																								
<b>C</b>	19.0 Nylon	35.0																																								
<b>*Q</b>	19.0 Nylon (+ chrome trim)	35.0																																								

## DIMENSIONS mm



## OPTIONS

### Sealing

Neoprene washers to seal between bezel and panel (W23) and lens and bezel (W24) to give a seal equivalent to IP66 are available on most versions.

### F0445 M0

P.V.C. Insulating terminal cover.



\*Note P and Q body codes denote a nylon body fitted with a chrome bezel trim (previously **F0413PO**).